

Lennite® is a Registered Trademark of Westlake Plastics Co.

Lennite ram extruded bar stock is made from UHMWPE resin which conforms to ASTM F648 and ISO 5834-1. Westlake Plastics' manufacturing processes and stringent quality control deliver well-consolidated and consistent pre-forms. Lennite ram extruded bar stock conforms to ASTM F648 and ISO 5834-2 and is targeted for use in machining orthopedic implants. Sterilization methods include EtO gas, cold sterilization, and limited gamma irradiation.





ISO 10993 & FDA COMPLIANT





## The following physical property information is based on testing performed on ram extruded Lennite rods.

Property (Type I)	Units	Requirement	GUR1020 Result
Density	kg/m³	927 to 944	.932
Delisity	Kg/III	927 10 944	.932
Ash Content	mg/kg	150 (max.)	58
Tensile Strength			
@yield	MPa	21 (min.)	22.6
@break	MPa	35 (min.)	49.9
Elongation @break	%	300 (min.)	405
Liongation @Break	70	300 (11111.)	103
Izod Impact Strength	kJ/m²	126 (min.)	NB
Property (Type II)	Units	Requirement	GUR1050 Result
Density	kg/m³	927 to 944	928
Ash Content	mg/kg	150 (max.)	60
Tensile Strength			
@yield	MPa	19 (min.)	20.5
@break	MPa	40 (min.)	44
Elongation @break	%	340 (min.)	381

## **Applications Include:**

- -Total hip and knee joint prosthesis
- -Various other surgical implants
- Medical devices

## **Manufacturing Capabilities:**



## **Colors:**



In addition to our standard capabilities, Westlake also has the ability to process custom resins in various sizes and colors with some exceptions.

This information is offered solely for your consideration, examination and verification, and is to be construed neither as a warranty nor guarantee that the same results as those stated herein will be obtained by the use to which others may put the material. Each user of the material should make his own tests to determine the characteristics and suitability of the material for his own particular use and the use which will be made of the completed product. This publication is not to be taken as a license to operate under, or a recommendation to infringe any patents. The observance of all legal regulations and patents is the responsibility of the user. The buyer's exclusive remedy against the seller shall be for the repair or replacement of defective stock. No other remedy (including, but not limited to, incidental or consequential damages for lost profits, lost sales, injury to person or property or other incidental or consequential damages.

kJ/m<sup>2</sup>



Izod Impact Strength

Phone : 1.610.459.1000 Phone : 1.800.000.1700 Fax : 610.459.1084

490 West Lenni road Lenni, PA 19052 U.S.A

Email: info@westlakeplastics.com

73 (min.)



NB



