

Zelux® is a Registered Trademark of Westlake Plastics Co.









INSULATING







Electrical Dreservice	Test Method		Result
Electrical Properties	rest method	Metric	English
Surface Resistivity dry	ASTM D257	10 ³ - 10 ⁶ ohm/sq	10 ³ - 10 ⁶ ohm/sq
Volume Resistivity dry	ASTM D257	10 ³ - 10 ⁶ ohm-cm	3937 - 39370080.00 ohm-in
Static decay	Mil-B-81705-B	< 0.1 seconds	< 0.1 seconds
Mechanical Properties	Test Method	Result	
		Metric	English
Tensile Strength at yeild	ASTM D638	65 MPa	9.4 kpsi
Tensile Elongation at break	ASTM D638	5 %	5 %
Flexural Strength	ASTM D790	107 MPa	15.5 kpsi
Flexural Modulus	ASTM D790	3172 MPa	460 kpsi
Izod Impact Strength Notched	ASTM D256	0.75 J/cm	1.4 ft-lb/in
Izod Impact Strength Un-notched	ASTM D256	5.3 J/cm	10 ft-lb/in
Hardness-Shore D	ASTM D2240	62	62
Other Properties	Test Method	Result	
		Metric	English
Specific Gravity	ASTM D792	1.32	1.32
Water Absorption at 24 hours	ASTM D570	0.16 %	0.16 %
Thermal Properties	Test Method	Result	
		Metric	English
Heat Deflection Temp. at 264 psi	ASTM D648	132 °C	270 °F
Flam. Rating-UL94	-	V-0 at 0.028	V-0 at 0.028
Coefficient of Thermal Expansion	ASTM D696	m/m/°C	in/in/°F
Thermal conductivity	-	watt-meter/K	BTU-in/hr-ft ² -°F

Applications Include:

- Semiconductor/electronic components
 Cassette housings
- Telecommunications hardware
- Explosives handling equipment

Manufacturing Capabilities:









Colors:



In addition to our standard capabilities, Westlake also has the abili to process custom resins in various sizes and colors with some exceptions.

This information is offered solely for your consideration, examination and verification, and is to be construed neither as a warranty nor guarantee that the same results as those stated herein will be obtained by the use to which others may put the material. Each user of the material should make his own tests to determine the characteristics and suitability of the material for his own particular use and the use which will be made of the completed product. This publication is not to be taken as a license to operate under, or a recommendation to infringe any patents. The observance of all legal regulations and patents is the responsibility of the user. The buyer's exclusive remedy against the seller shall be for the repair or replacement of defective stock. No other remedy (including, but not limited to, incidental or consequential damages for lost profits, lost sales, injury to person or property or other incidental or consequential damages.



Phone: 1.610.459.1000 Phone: 1.800.000.1700 Fax: 610.459.1084

490 West Lenni road Lenni, PA 19052 U.S.A

Email:info@westlakeplastics.com





