

Zelux® is a Registered Trademark of Westlake Plastics Co.

Zelux W is an optically clear engineering plastic with excellent dimensional stability and good strength and stiffness over a wide range of service temperatures. Zelux is used for a wide variety of electrical applications due to its low moisture absorption, good electrical insulating properties (Dielectric Strength 760 v/mil) and an excellent flammability rating (UL Yellow Card file E240206). Zelux is easy to fabricate, paint, and glue.



Property	Units	Test StandardR	esult
Mechanical			
Flexural Modulus	psi	ASTM D790	339,000
Flexural Strength @yield	psi	ASTM D790	14,100
lzod Impact Strength Notched @73°F Un-Notched	ft•lbs/in ft•lbs/in	ASTM D256 ASTM D256	17.0 60.0
Tensile Elongation @break	%	ASTM D638	135.0
Tensile Strength @break @yield	psi psi	ASTM D638 ASTM D638	9,900 8,900
Thermal			
Coefficient of Thermal Expansion	in/in/°F	ASTM E831	3.44x10 <sup>-5</sup>
Heat Deflection Temperature @66 psi (.250") @264 psi (.250")	°F °F	ASTM D648 ASTM D648	280 270
Other			
Specific Gravity		ASTM D792	1.20

## **Applications Include:**

- Transparent Impact Shields
- Transparent Fluid Handling Components
- Transparent Manifolds
- Transparent Impact resistant housings and Covers
- Transparent Prototyping Parts
- Electrical Insulating Components
- Metal Replacement / Weight Reduction

## **Manufacturing Capabilities:**



## **Colors:**

Translucent White

This information is offered solely for your consideration, examination and verification, and is to be construed neither as a warranty nor guarantee that the same results as those stated herein will be obtained by the use to which others may put the material. Each user of the material should make his own tests to determine the characteristics and suitability of the material for his own particular use and the use which will be made of the completed product. This publication is not to be taken as a license to operate under, or a recommendation to infringe any patents. The observance of all legal regulations and patents is the responsibility of the user. The buyer's exclusive remedy against the seller shall be for the repair or replacement of defective stock. No other remedy (including, but not limited to, incledental or consequential damages for lost profits, lost sales, injury to person or property, or other incidental or consequential loss) shall be available to the buyer.



Phone : 1.610.459.1000 Phone : 1.800.000.1700 Fax : 610.459.1084 490 West Lenni road Lenni, PA 19052

U.S.A Email : info@westlakeplastics.com





EXCLUSION OF WARRANTIES: THERE ARE NO WARRANTIES AS TO THE MATERIAL DES-CRIBED HEREIN, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE. ANY VALUES STATED IN SELLER? IS LITERATURE ARE TYPICAL PROPERTIES ONLY.